

216CR NEXT PURSUIT, 42D18 NEXT PURSUIT LOGO*

Flammability	
Pill Test	PASS
(CPSC FF1-70)	
Flooring Radiant Panel	
(ASTM E-648) Direct Glue	
NBS Smoke Density	
(ASTM-E662)	
Flaming Mode	< 450
Non-Flaming Mode	< 450
Tunnel Test	
(ASTM-E662)	
Corner Burn Test	
(UBC-82)	
Automotive Flammability	
(FMVSS-302)	
Acoustic	
Noise Reduction Coefficient	
Gypsum	
Acoustic Backer	
Static	
AATCC-134	
Type Static Control	STATIC RESISTANT
FHA DATA UM44D	
Certification Number	
Warranties	3-YEAR INDOOR/OUTDOOR
CRI Certification	CALL 1-800-441-7429

217CR NEXT PURSUIT SG - 42D19 NEXT PURSUIT LOGO SG*

Flammability	
Pill Test	PASS
(CPSC FF1-70)	
Flooring Radiant Panel	
(ASTM E-648) Direct Glue	
NBS Smoke Density	
(ASTM-E662)	
Flaming Mode	
Non-Flaming Mode	
Tunnel Test	
(ASTM-E662)	
Corner Burn Test	
(UBC-82)	
Automotive Flammability	

(FMVSS-302)

Acoustic

Noise Reduction Coefficient

Gypsum

Acoustic Backer

Static

AATCC-134

Type Static Control

STATIC RESISTANT

FHA DATA UM44D

Certification Number

Warranties

3-YEAR INDOOR/OUTDOOR

CRI Certification

CALL 1-800-441-7429

NEXT PURSUIT 06-00

Flammability

Pill Test

PASS

(CPSC FF1-70)

Tunnel Test

(ASTM-E662)

Corner Burn Test

(UBC-82)

Automotive Flammability

(FMVSS-302)

Acoustic

Noise Reduction Coefficient

NRC

Gypsum

Acoustic Backer

Warranties

3-YEAR INDOOR/OUTDOOR

CRI Certification

Green Label Plus:

GLP9989

Durability Rating:

Except where noted as a minimum or maximum, the above specifications are nominal and, therefore, are subject to change and to normal manufacturing variance.

*Styles 42D18 and 42D19 minimum order quantity is 800 SY per color and backing.