

## Passages II - Product Data

### Flammability

**Pill Test** PASS

(CPSC FF1-70)

### Flooring Radiant Panel

(ASTM E-648) Direct Glue

### NBS Smoke Density

(ASTM-E662)

**Flaming Mode** < 450

**Non-Flaming Mode** < 450

### Tunnel Test

(ASTM-E662)

### Corner Burn Test

(UBC-82)

### Automotive Flammability

(FMVSS-302)

### Acoustic

#### Noise Reduction Coefficient

#### Gypsum

#### Acoustic Backer

#### Static

**AATCC-134** < 3.5 KV

**Type Static Control** STATIC RESISTANT

### FHA DATA UM44D

### Certification Number

### Warranties

5-YEAR

INDOOR/OUTDOOR -

5-YEAR SOFT SPIKE

**CRI Certification** CALL 1-800-441-7429

## Passages II Tile - Product Data

### Flammability

**Pill Test** PASS

(CPSC FF1-70)

### Flooring Radiant Panel

(ASTM E-648) Direct

Glue

### NBS Smoke Density

(ASTM-E662)


**Flaming Mode** < 450

**Non-Flaming Mode** < 450

### Tunnel Test

(ASTM-E662)  
**Corner Burn Test**  
(UBC-82)  
**Automotive  
Flammability**  
(FMVSS-302)  
**Acoustic  
Noise Reduction  
Coefficient**  
**Gypsum  
Acoustic Backer**  
**Static  
AATCC-134**  
**Type Static Control**      STATIC RESISTANT  
**FHA DATA UM44D**  
**Certification Number**  
**Warranties**              LIFETIME COMMERCIAL LIMITED  
**CRI Certification**        CALL 1-800-441-7429

Except where noted as a minimum or maximum, the above specifications are nominal and, therefore, are subject to change and to normal manufacturing variance.



**CARPET TILE RECOMMENDED  
INSTALLATION METHOD:  
Quarter Turn**