

## Stride II

<b>Style Number / Name</b>	245CR STRIDE II	246CR Stride II TILE
<b>Flammability</b>		
<b>Pill Test</b> (CPSC FF1-70)	PASS	PASS
<b>Flooring Radiant Panel</b> (ASTM E-648)	CLASS I	CLASS I
<b>NBS Smoke Density</b> (ASTM-E662)		
<b>Flaming Mode</b>	< 450	< 450
<b>Non-Flaming Mode</b>	< 450	< 450
<b>AACHEN</b>	N/A	PASS
<b>Static Cof-Frict</b>		
<b>ASTM C1025</b>	0.79 TBD	0.70
<b>AATCC134</b>	< 3.5 KV	< 3.5 KV
<b>Xenon</b>		
<b>AATCC 16 Degradation</b>	1,000 hrs no degradation	1,000 hrs no degradation
<b>AATCC 16 Colorfastness</b>	100 hrs 4.0 rating	100 hrs 4.0 rating
<b>AATCC 129 Ozone Fade</b>	4.0 RATING	4.0 RATING
<b>Contract Velcro</b>	> 3.0	3.0
<b>WARRANTIES</b>	LIFETIME COMMERCIAL	LIFETIME COMMERCIAL
<b>Green Label Plus</b>	PASS / GLP9168 / 56X	PASS / GLP0520 / 38X
<b>Cradle to Cradle Certified</b>	Silver	Silver
<b>NSF-140 Certified</b>	N/A	Platinum (reg. no. SCS-SCC-01819)

## Ravine

<b>Style Number / Name</b>	247CR RAVINE	248CR RAVINE TILE
<b>Flammability</b>		
<b>Pill Test</b> (CPSC FF1-70)	PASS	PASS
<b>Flooring Radiant Panel</b> (ASTM E-648)	CLASS I	CLASS I
<b>NBS Smoke Density</b> (ASTM-E662)		
<b>Flaming Mode</b>	< 450	< 450
<b>Non-Flaming Mode</b>	< 450	< 450
<b>AACHEN</b>	N/A	N/A
<b>Static Cof-Frict</b>		
<b>ASTM C1025</b>	0.69	0.70
<b>AATCC134</b>	< 3.5 KV	< 3.5 KV
<b>Xenon</b>		
<b>AATCC 16 Degradation</b>	1,000 hrs no degradation	1,000 hrs no degradation
<b>AATCC 16 Colorfastness</b>	100 hrs 4.0 rating	100 hrs 4.0 rating

<b>AATCC 129 Ozone Fade</b>	4.0 RATING	4.0 RATING
<b>Contract Velcro</b>	4.0	3.0
<b>WARRANTIES</b>	LIFETIME COMMERCIAL	LIFETIME COMMERCIAL
<b>Green Label Plus</b>	PASS / GLP9168 / 56X	PASS / GLP0520 / 38X
<b>Cradle to Cradle Certified</b>	Silver	Silver
<b>NSF-140 Certified</b>	N/A	Platinum (reg. no. SCS-SCC-01819)

## Incline

<b>Style Number / Name</b>	249CR INCLINE TILE
<b>Flammability</b>	
<b>Pill Test</b>	PASS
(CPSC FF1-70)	
<b>Flooring Radiant Panel</b>	CLASS I
(ASTM E-648)	
<b>NBS Smoke Density</b>	
(ASTM-E662)	
<b>Flaming Mode</b>	< 450
<b>Non-Flaming Mode</b>	< 450
<b>AACHEN</b>	PASS
<b>Static Cof-Frict</b>	
<b>ASTM C1025</b>	0.92
<b>AATCC134</b>	< 3.5 KV
<b>Xenon</b>	
<b>AATCC 16 Degradation</b>	1,000 hrs no degradation
<b>AATCC 16 Colorfastness</b>	100 hrs 4.0 rating
<b>AATCC 129 Ozone Fade</b>	4.0 RATING
<b>Contract Velcro</b>	3.5
<b>WARRANTIES</b>	LIFETIME COMMERCIAL
<b>Green Label Plus</b>	PASS / GLP0520 / 38X
<b>Cradle to Cradle Certified</b>	Silver
<b>NSF-140 Certified</b>	Platinum (reg. no. SCS-SCC-01819)

Except where noted as a minimum or maximum, the above specifications are nominal and, therefore, are subject to change and to normal manufacturing variance.

\*Styles 42D18 and 42D19 minimum order quantity is 800 SY per color and backing.